


LAMP PHOTOMETRIC REPORT

MODEL: 99PFMT30/WH		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1531.4 lm



$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%
10	550.6	550.4	549.7	548.1	546.8	545.9	547.4	549.4	0- 10	53.02	53.02	3.46
20	514.5	514.2	512.7	510.7	506.8	505.2	508.1	512.8	10- 20	150.1	203.1	13.3
30	458.2	466.0	455.4	472.0	448.1	445.3	449.3	457.0	20- 30	223.1	426.3	27.8
40	397.8	403.2	411.3	400.5	392.7	372.6	377.6	398.6	30- 40	266.8	693.1	45.3
50	333.5	329.4	305.0	325.7	311.7	293.3	303.9	314.9	40- 50	272.8	965.9	63.1
60	250.2	241.7	220.9	237.3	232.0	211.5	216.5	231.7	50- 60	243.6	1210	79
70	156.5	148.7	137.1	143.8	144.4	130.9	134.7	145.7	60- 70	183.1	1393	90.9
80	66.63	62.48	67.36	60.71	61.12	56.86	60.06	64.60	70- 80	106.1	1499	97.9
90	5.895	2.036	14.45	1.409	4.126	1.479	5.847	2.125	80- 90	32.65	1531	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 10.0DEG  
 Test Speed: MEDIUM  
 Temperature: 25.3°C  
 Operators:  
 Test Date: 15 November 2022

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 2.5DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.00.456  
 Humidity: 65.0%  
 Test Distance: 6.265m [K=1.0000]  
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```