


LAMP PHOTOMETRIC REPORT

MODEL: 99POMT40/WH		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 1488.3 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	563.1	562.7	561.7	559.8	558.0	557.7	559.5	561.9	0- 10	54.14	54.14	3.64
20	526.6	524.7	523.6	521.3	517.7	516.4	520.1	525.2	10- 20	153.4	207.5	13.9
30	468.1	465.2	464.4	462.6	457.6	454.7	460.3	467.8	20- 30	227.7	435.2	29.2
40	394.4	389.5	389.1	388.5	383.4	377.8	385.3	394.6	30- 40	266.8	702.0	47.2
50	310.5	305.1	303.2	305.4	299.6	294.1	300.9	312.3	40- 50	267.3	969.3	65.1
60	221.7	216.6	214.2	217.6	211.8	208.1	213.7	225.4	50- 60	232.8	1202	80.8
70	131.7	128.7	127.3	130.8	126.1	123.2	127.8	138.3	60- 70	170.6	1373	92.2
80	50.44	48.53	49.00	51.43	47.11	45.98	49.73	57.53	70- 80	93.23	1466	98.5
90	1.989	1.279	7.729	1.320	1.640	1.109	2.826	1.360	80- 90	22.37	1488	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:15 November 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```